



■ SPECIFICATION

Operating weight	9600 kg
Max. lifting capacity at maximum height	2000 kg
Excavator bucket capacity	0.3 m³
Loader bucket capacity	1.2 m³
Maximum digging force	5100 kgf
Backhoe boom swing angle	190°
Bucket breakout force	54 kN
Hydraulic system	PWG (Italy)
Steering system	Danfoss
Drive axle	XCMG
Electronically controlled transmission	4 forward / 3 reverse gears
ROPS cab with air-conditioning	Yes
Italian load-sensing valve + piston pump	Yes
Rear-view camera	Yes
Telescopic rear boom	Yes
Motion stabilization system	Yes
2WD/4WD switch	Yes
Rear hydraulic line for breaker	Yes
Seat-integrated joystick	Yes
6-in-1 multifunction bucket	Yes

■ ENGINE

Model	Weichai
Type	Inline, 4-stroke diesel with direct injection
Rated power	74 kW (100 KM)
Rated speed	2200 rpm
Emission	Euro V

■ DIMENSIONS

Total length (with folded boom)	5934 mm
Total width	2220 mm
Cab height	2950 mm
Max. working height	6246 mm
Max. loading height	4270 mm
Max. digging depth	4643 mm
Max. reach from swing center	6420 mm
Max. hinge height	3500 mm
Digging depth below ground	100 mm
Dump reach at full lift	1180 mm
Max. dump height at 45°	2829 mm
Boom height	3506 mm
Wheelbase	2285 mm
Dump angle	55°
Bucket rotation angle	200°

