



## ■ SPECIFICATION

|                        |                  |
|------------------------|------------------|
| Model                  | GT950            |
| Weight                 | 960 kg           |
| Engine                 | Koop 192F Euro 5 |
| Power                  | 9.5 hp           |
| Bucket width           | 420 mm           |
| Inverted boom cylinder | Yes              |
| Swing boom             | Yes              |
| Retractable tracks     | Yes              |

## ■ HYDRAULIC SYSTEM AND DRIVE

|                |          |
|----------------|----------|
| Main pump      | Tianji   |
| Control valve  | Beifang  |
| Slewing motors | Like     |
| Drive motors   | Like     |
| Flow rate      | 16 l/min |
| Pressure       | 16 MPa   |

## ■ WORKING RANGE

|                                     |         |
|-------------------------------------|---------|
| Max. digging radius at ground level | 2430 mm |
| Max. digging depth                  | 1680 mm |
| Max. digging height                 | 2490 mm |
| Max. dump height                    | 1760 mm |
| Minimum slewing radius              | 1190 mm |
| Min. digging radius                 | 1340 mm |
| Max. blade lift height              | 175 mm  |
| Max. blade digging depth            | 325 mm  |

## ■ DIMENSIONS

|                            |         |
|----------------------------|---------|
| Overall length             | 2650 mm |
| Overall height             | 2200 mm |
| Overall width              | 930 mm  |
| Total track length         | 1100 mm |
| Platform tail swing radius | 733 mm  |
| Platform ground clearance  | 380 mm  |
| Undercarriage width        | 950 mm  |
| Track width                | 180 mm  |
| Track height               | 320 mm  |

