



■ SPECIFICATION

Engine Brand:	Yanmar
Engine Model:	4TNV98C-PLYS
Maximum Power (HP):	67.86
Maximum Power (kW):	49.9
Maximum RPM:	2400 rpm
Displacement:	3.319 L
Number of Cylinders:	4
Cooling Method:	Water-cooled
Engine Oil Capacity (during change):	7 L
Fuel Type:	Diesel
Theoretical Fuel Consumption:	7.52 - 8.78 L/h
Machine Operating Weight:	4150 kg
Bucket Capacity:	0.4 m³
Nominal Load Capacity (Safe Load):	1050 kg
Maximum Load Capacity:	2100 kg
Drive Pump Model:	HP21VG45 Closed Pump
Drive Pump Brand:	Hengli
Maximum Flow of Drive Pump:	108 + 108 L/min
Work Pump Model:	TFA10VO45/53R Piston Pump
Main Pump Brand:	Taifeng
Maximum Flow of Main Pump:	108 L/min
Multiway Valve:	Load-sensitive multiway valve
Nominal Pressure:	21 MPa
Hydraulic Motor Type:	LX21VP45
Travel Motor:	Lezhuo
Engine Capacity (Travel Motor):	45

■ WORKING RANGE

Travel Speed:	Low: 0-5 km/h, High: 0-10 km/h
Climbing Ability:	30%
Fuel Tank Capacity:	45 L
Hydraulic Tank Capacity:	56 L

■ MAXIMUM DUMPING HEIGHT:

Maximum Dumping Height:	2250 mm
Maximum Loading Height:	3600 mm
Farthest Dumping Reach:	1360 mm
Minimum Ground Clearance:	231 mm
Transport Length with Bucket:	3820 mm
Transport Length without Bucket:	3040 mm
Transport Width:	1800 mm
Transport Height:	2460 mm
Bucket Width:	1800 mm
Crawler Length:	320 mm
Crawler Width:	84 mm
Number of Crawler Sections:	52

■ ZUSÄTZLICHES ZUBEHÖR

Bale grab

Earth auger

Grass grab

Crocodile grab

Pallet forks

4-in-1 bucket

Mower

Snow plow

Quick coupler

